

PARIN, V.V.; MEYERSON, F.Z.

Role and problems in experimental cardiology. Vest.AMN SSSR 16
no.5:5-12 '61. (MIRA 14:12)

1. Institut normal'noy i patologicheskoy fiziologii AMN SSSR.
(CARDIOLOGY)

KHOKHINA, Ye.M.; MEYERSON, F.Z.; MIKHELYAN, A.L.

Dynamics of morphological changes in the intramural neural apparatus
in compensatory hyperfunction of the heart. Biul. eksp. biol. i med.
52 no.10:115-118 0 '61.
(MIRA 15:1)

1. Iz laboratorii neyrogistologii imeni B.I.Lavrent'yeva (zav. -
prof. Ye.K. Plechkova) i laboratorii fiziologii i patofiziologii
serdechnoy deyatel'nosti Instituta normal'noy i patologicheskoy
fiziologii (dir. - deystvitel'nyy chlen AMN SSSR V.V.Parin) Akad.
SSSR, Moskva. Predstavlena deystvitel'nyy chlenom AMN SSSR
V.V.Parinyam.

(HEART__INNERVATION)

MEYERSON, F.Z.; PSHENNIKOVA, M.G.; RAMENSKAYA, G.P.; CHERNYSHEVA, G.V.

Experimental prophylaxis of some changes developing in the myocardium during chronic heart failures. Dokl. AN SSSR 141 no.2: 509-512 N '61. (MIRA 14:11)

1. Institut normal'noy i patologicheskoy fiziologii Akademii meditsinskikh nauk SSSR. Predstavleno akademikom L.S.Shtern. (HEART FAILURE)

MEYERSON, F.Z., MANUKHIN, B.N., PSHENNIKOVA, M.G., ROZANOVA, L.S. 3

"On the intermediate metabolism of the myocardium in compensatory hyperfunction and hypertrophy of the heart."

Report submitted, but not presented at the 22nd International Congress of Physiological Sciences.
Leiden, the Netherlands 10-17 Sep 1962

PARIN, V.V.; MEYERSON, F.Z.;

[Myocardial tension and the functional reserve of the heart]
Napriazhenie miokarda i funktsional'nyi rezerv serdtsa; ma-
terialy doklada na konferentsii in-ta 14-15 iunia. Moskva,
in-t normal'noi i patologicheskoi fiziologii, 1962. 21 p.
(HEART--MUSCLE) (MIRA 15:7)

MEYERSON, F.Z.; MIKAELYAN, A.L.; MARKOVSKAYA, G.I.;

Function of the right ventricle of the heart under conditions of progressing stress on the left ventricle and left ventricular insufficiency. Zhur. eksp. i klin. med. 2 no.6:3-13 '62.

(MIRA 18:10)

1. Institut normal'noy i patalogicheskoy fiziologii AMN SSSP i Institut kardiologii i serdechnoy khirurgii AN ArmSSR.

MEYERSON, F.Z.

Senile changes developing in the myocardium under the influence of
cardiac hyperfunction and their experimental prevention. Zhur. ob.
biol. 23 no.2:114-118 Mr-Apr '62. (MIRA 15:5)

1. Institute of Normal and Pathological Physiology, U.S.S.R.
(HEART—MUSCLE)

MEYERSON, F.Z.; DMITRIYEVA, T.M.

Effect of cardiac hyperfunction on the establishment of the
negative chronotropic effect of the vagus nerve. Dokl.AN SSSR
145 no.5:1184-1187 '62. (MIRA 15:8)

1. Institut normal'noy i patologicheskoy fiziologii AMN SSSR.
Predstavleno akademikom A.N.Bakulevym.
(VAGUS NERVE) (HEART)

MEYERSON, F.Z.; MONAYENKOV, A.M.

Anticardiac autoantibodies in cardiac hypertrophy. Dokl. AN SSSR
145 no.6:1421-1423 Ag '62. (MIRA 15:8)

1. Institut normal'noy i patologicheskoy fiziologii AMN SSSR.
Predstavleno akademikom A.N.Bakulevym.
(ANTIGENS AND ANTIBODIES) (HEAT FAILURE)

MEYERSON, F.Z.

[Interrelationship of the physiological function and the genetic apparatus of the cell] O vzaimosvrazi fiziologicheskoi funktsii i geneticheskogo apparata kletki; materialy doklada na konferentsii instituta. Moskva, In-t normal'noi i patologicheskoi fiziologii AMN SSSR, 1963. 91 p.

(CYTOLOGY)

(MIRA 16:6)

MEYERSON, F.Z.; MIKAYELIAN, A.L.; SHENDEROV, S.M.; MARKOVSKAYA, G.I.

Dynamics of stress in the myocardium in compensatory hyperfunction and insufficiency of the heart from overwork.
Zhur. eksp. i klin. med. 3 no.4:13-23 '63. (MIRA 16:12)

1. Institut normal'noy i patologicheskoy fiziologii AMN SSSR
i Institut kardiologii i serdechnoy khirurgii AN Armyanskoy
SSR.

MEYERSON, F.Z.; MARKOVSKAYA, G.

Energy transformation in the heart. Cor vasa 5 no.2:81-89 '63.

1. Institute of Normal and Pathological Physiology, Academy of
Medical Sciences, Moscow.

(ENERGY METABOLISM)

(MYOCARDIUM)

(HEART)

(AORTIC STENOSIS)

MEYER, J. A. (1964) *Ann. N.Y. Acad. Sci.*

Inhibition of the heart by the vagus nerve in the presence of
hypertension. The heart rate is decreased by the vagus nerve
the heart rate is decreased by the vagus nerve.

1. Inhibition of the
cardiac will be shown.

MEYERSON, F.Z.; BELOSHAPKINA, T.D.; LISHNIKOV Ye.F.; LEYKINA, Ye.M.;
MARKOVSKAYA, G.I.; CHERYZHOVA, G.V.

Function, structure and protein metabolism of hypertrophied
myocardium. Vestn. Akad. med. nauk SSSR 18 no. 3:27-31, 1963
(MIRA 13:1)

1. Institut normal'noy i patologicheskoy fiziologii AMN SSSR,
I Moskovskiy nauchno issledovatel'skiy institut imeni I.M.
Sechenova Institut eksperimental'noy biologii AMN SSSR.

KROKHINA, Ye.M.; MEYERSON, F.Z.

(Moskva)

Dynamics of cholinesterase activity in the neural apparatus of the heart and myocardium in compensatory hyperfunction and hypertrophy. Arkh. pat. 25 no.8:34-37 '63 (MIRA 17:4)

1. Iz laboratorii neyrogistologii imeni B.I. Lavrent'yeva (zav. - prof. Ye.K. Plechkova) i laboratorii fiziologii i patologii serdtsa (zav. - deystvitel'nyy chlen AMN SSSR. V.V. Parin) Instituta normal'noy i patologicheskoy fiziologii AMN SSSR (direktor - deystvitel'nyy chlen AMN SSSR V.V. Parin).

MEYERSON, F.Z. LEYKINA, Ye.M.; BELOSHAPKINA, T.D.

Interrelation between the physiological function and genetic apparatus of a cell. Dokl.AN SSSR 149 no.3:700-702 Mr '63.
(MIRA 16:4)

1. Institut normal'noy i patologicheskoy fiziologii AN SSSR.
Predstavleno akademikom A.N.Bakulavym.

(Heart→Muscle)

(Cell metabolism)

(Nucleic acids)

MEYERSON, F.Z.; SADOVSKAYA, L.Yu.; POGOSYAN, L.A.

Blocking role of sulfhydryl groups in the mechanism of the
action of cardiac glycosides. Dokl. AMN SSSR 150 no.3:702-704
My '63. (MIRA 16:6)

1. Institut normal'noy i patologicheskoy fiziologii AMN SSSR.
Predstavleno akademikom A.N. Bakulevym.
(Cardiac glycosides)
(Mercapto group)

MEYERSON, F.Z.; MALOV, G.A.; PSHENNIKOVA, M.G.; KALEBINA, N.S.

Correlation in the intensity of synthesis and the breakdown
of protein in the myocardium in heart hyperfunction. Dokl.
AN SSSR 154 no. 3:738-741 Ja '64. (MIRA 17:5)

1. Institut normal'noy i patologicheskoy fiziologii AMN SSSR
i Institut serdechno-sosudistoy khirurgii AMN SSSR. Predstavleno
akademikom A.N.Bakulevym.

MEYERSON, F.Z.; ZALETAYEVA, T.A.; LAGUCHEV, S.S.; PSHENNIKOVA, M.G.

Correlation of the mass of energy-producing and functioning structures in the adaptation process of the differentiated cell to a prolonged increase in functional level. Dokl. AN SSSR 157 no.3:668-672 J1 '64.
(MIRA 17:7)

1. Institut normal'noy i patologicheskoy fiziologii AMN SSSR i Institut eksperimental'noy biologii AMN SSSR. Predstavleno akademikom A.N. Belozerskim.

MEYERSON, I. I. I. D. FAR VA, L.S.

Effect of changes in mediator metabolism on the development of
heart hypertrophy. Biol. eksp. biol. i med. 1974, 113, 164.
164.

1. Institut normal'nyy i patologicheskoy fiziol. i med. i med.
vital'nyy chlen AMN SSSR prof. V.V. Parin. AMN SSSR, Moscow

KROKHINA, Ye.M.; MEYERSON, F.Z.

Dynamics of the content of nucleic acids in intramural nerve
neurons in compensatory hyperfunction of the heart. Trudy Inst.
norm. i pat.fiziol. AMN SSSR 7:55-56 '65. (MIRA 18:6)

1. Laboratoriya neyrogistologii (zav. - Ye.K.Plechko) i
laboratoriya fiziologii i patologii miokarda (zav. doktor med.
nauk F.Z.Meyerson) Instituta normal'noy i patologicheskoy
fiziologii AMN SSSR.

CHEZNYNSHEVA, G.V.; MEYERSON, F.Z.

Dynamics of the enzymatic activity of myocardial myosin in compensatory cardiac hyperfunction. Vop. med. khim. 11 no.2:17-20 Mr-Apr '65.

(MIRA 18:10)

1. Laboratoriya biokhimi i laboratoriya fiziologii i patologii serdechnoy deyatel'nosti Instituta normal'noy i patologicheskoy fiziologii AMN SSSR, Moskva.

ME:FRSON

FEL'DMAN, S.B.; MEYERSON, F.L.; MARKOVSKAYA, G.I.; SHENKIN, I.M.;
KHIL'KIN, A.N.

Comparative studies on the duration of systole and on in-
tracardiac hemodynamics in progressively experimental aortic
diseases. Kardiologiya 5 no.2:22-31 Apr-May 1965. (M) 2:127

1. Propedevticheskaya terapevticheskaya klinika (zav. -
deystvitel'nyy chlen ANU SSSR prof. V.Kh.Vasil'nyy) i
Moskovskogo meditsinskogo Instituta imeni I.I. Mechnikova
i laboratoriya fiziologii i patologii serdtsa Instituta
normal'noy i patologicheskoy fiziologii (direktor -
deystvitel'nyy chlen ANU SSSR prof. V.V.Parin). (M) 2:127

PARIN, Vasil'y Vasil'yevich; MEYERSON, Feliks Zal'manovich;
CHENIL'OV, S.K., red.

[Studies on the clinical physiology of blood circulation]
Ocherki klinicheskoi fiziologii krovoobrashcheniia. Mo-
skva, Meditsina, 1965. 209 p. (MIRA 18:8)

SPIRICHEV, V.B.; MEYERSON, F.Z.; D'YACHKOV, L.V.; BLAZHEYEVICH, N.V.

Effect of compensatory hyperfunction and hypertrophy of the heart on the content of vitamins B₁, B₂ and B in the myocardium and liver in rabbits. Vop. med. khim. 11 no.2:54-59 Mr-Apr '65.

(MTO 18:10)

1. Gosudarstvennyy nauchno-issledovatel'skiy institut vitaminologii Ministerstva zdravookhraneniya SSSR i Institut normal'noy i patologicheskoy fiziologii AMN SSSR, Moskva.

L 34187-66 EWT(1)/T JK

ACC NR: AP6026015

SOURCE CODE: UR/0247/66/016/002/0274/0291

AUTHOR: Meyerson, F. Z. (Moscow); Kruglikov, R. I. (Moscow)

ORG: none

TITLE: Interrelationship of the genetic apparatus with the physiological function of the neuron as a factor in the mechanism of conditioned reflexes and memory

SOURCE: Zhurnal vysshey nervnoy deyatel'nosti, v. 16, no. 2, 1966, 274-291

TOPIC TAGS: conditioned reflex, neuron, animal physiology, animal genetics, RNA, DNA, cytology, biologic metabolism

ABSTRACT: In the course of this survey of the pertinent published literature it is established that the reinforcement of new conditioned reflexes requires an adequate synthesis of RNA on DNA templates whereas, on the other hand, previously established firm reflexes may persist fairly long despite the inhibition of DNA-dependent synthesis of RNA. On the basis of experiments with the effect of the inhibition of protein synthesis on conditioned reflexes and memory, involving the use of the antibiotic puromycin, which inhibits the transport of amino acids and ribosomes and disturbs their protein synthesis, it is established that intracerebral administration of ribonuclease leads to the same effects as the administration of puromycin -- the destruction of the developed conditioned reflexes. An analysis of the findings of various investigators on the role of nucleic acid synthesis in the mechanism of conditioned reflexes and memory gives considerable reason to believe that the realization of intra-neuron interrelationship between the genetic apparatus of the cell and the cell's function plays a decisive role in the formation of inter-neuron connections as well as in the formation of the multi-neuron systems representing the structural basis for the reinforcement of conditioned reflexes and memory. The tests were carried out at the Laboratory of Neuroradiology/headed by Professor I. A. Piontkovskiy, Institute of Higher Nervous Activity and Neurophysiology, AN SSSR.

SUB CODE: 06 / SUBM DATE: 15Jun65 / ORIG REF: 045 / OTH REF: 077
Card 1/1

UDC: 612.833.81

RUBEL', V.M.; APANASYUK, M.P. [deceased]; MEYERSON, F.Z.

Metabolism of myocardial substances in compensatory hyperfunction of the heart. Myocardial carbonic anhydrase activity in compensatory hyperfunction and hypertrophy of the heart. Vop. med. khim. 9 no.1:57-60 Ja-F '63.

(MIRA 17:6)

1. Laboratoriya fiziologii i patofiziologii serdechnoy deyatel'nosti i laboratoriya biokhimii, Institut normal'noy i patologicheskoy fiziologii AMN SSSR, Moskva.

MIKAYELYAN, Aleksandr L'vovich. Prinsipal uchastiv. MEYERSON, F Z ,
doktor med. nauk; GRIGORYAN, E.A.; KYANDARYAN, K.A.; ~~dit's: red.~~

[Clinical pathophysiological changes in stenosis of the
left atrioventricular opening of the heart and its surgical
correction] Kliniko-patofiziologicheskie izmeneniia pri
suzhenii levogo atrioventrikuliarnogo otverstia serdtsa i
khirurgicheskaiia korrektsiia ego. Erevan, Aistat, 1964.
265 p. (MIRA 18:5)

1. Direktor Instituta kardiologii i serdechnoy khirurgii
AMN SSSR (for Kyandaryan).

MAYZELIS, M.Ya.; BAZARDZHIAN, A.G.; MEYERSON, F.Z.

Use of the products of glucose decomposition in protein synthesis following the compensatory hyperfunction of some organs. Dokl. AN Arm. SSR 39 no. 3:181-186 '64. (MIRA 18:1)

1. Institut normal'noy i patalogicheskoy fiziologii AMN SSSR. Predstavleno akademikom AN ArmSSR G.Kh.Bunyatyanom.

MEYERSON, F.Z.; POGOSOVA, A.V.

Incorporation of labeled amino acids into the total proteins
and proteins of myocardial nuclei in compensated hyperfunction
and hypertrophy of the heart. Vop. med. khim. 8 no.6:621-624
N-D '62. (CIBA 17:5)

1. Institut khirurgii imeni A.V. Vishnevskogo AMN SSSR i Institut
normal'noy i patologicheskoy fiziologii AMN SSSR, Moskva.

PARIN, V.V.; MEYERSON, F.L.

Myocardial stress and functional reserve of the heart in
hyperfunction and insufficiency. Vest. AMN SSSR 18 no.2:
20-32 '63. (MIRA 17:7)

1. Institut normal'noy i patologicheskoy fiziologii AMN SSSR.

"APPROVED FOR RELEASE: 07/19/2001

CIA-RDP86-00513R001033720016-8

1956-1957

APPROVED FOR RELEASE: 07/19/2001

CIA-RDP86-00513R001033720016-8"

MEYERSON, Prof. Grigoriy Abramovich


Dr. Technical Sci. Prof. Moscow Inst. Nonferrous Metals Goldm. M. I.
Kalinin, 1948 Ch. Engr., Main Admin. Rare Metals Ind., -1935-; Docent Bur. Hard
Alloys, -1935-. "Review of M. Yu. Bal'shin's Book 'Powdered Metal Studies',"
Stal'. No. 7, 1948. Stalin 2nd Prize, 1945, tantal en. tantalic alloy;
Stalin 3rd Prize, 1947, hard alloys.

Hard alloys from tungsten and molybdenum carbides. G. A. Meerson, Russ.
18,476, Aug. 31, 1960. Powder W and Mo carbides are pressed and heat-treated in the
presence of a binder consisting of an alloy of Co and W obtained by mixing solns. of
 NH_4WO_4 and $\text{Co}(\text{NO}_3)_2$ with the addn. of the hydrate of tungstic acid, concg. by
A. atm. to sirupy consistency, agitating for a number of hrs. in a porcelain mill, drying,
heating to 750°C, disintegrating and reducing in a H₂ atm. at red heat.

Page fortification from wolframite through ferrous tungstate (L. A. Muehlen
L. Appl. Chem. (U. S. S. R.) 6, 211-14 (1931). Lab. data show possibilities for the fol-
(fusion with Na_2CO_3) lowing process: Wolframite $\rightarrow \text{FeWO}_4$ (with FeSO_4 or FeCl_3)
 FeWO_4 (reduction with C etc.) $\rightarrow \text{FeW} \rightarrow \text{Na}_2\text{WO}_4$ $\rightarrow$

V. KALICHBEV

V. A. ALKHOVSKY




Composition for brazing working surfaces to tools
 A. Mironov and R. L. Veller. Russ. 644,734, July 27,
 1975. A mixt. of oxides of at least two of the metals Mo,
 Ti, W, V, Cr, Nb, Ta and Mn with the required amount
 of C is subjected to the aluminothermal reduction,
 powdered, and mixed with the amt. of an organic cement-
 ing substance and carbon required for the formation of
 carbides in the brazing process.

ASB 31.4 METALLURGICAL LITERATURE CLASSIFICATION

12001 510 02100

12001 510 02100



1ST AND 2ND SERIES										3RD AND 4TH SERIES									
PROCESSES AND PROPERTIES INDEX																			
<i>Influence of an Excess of Tungsten on the Properties of the Alloy Fedak and Substitution of Cobalt by Nickel. O. A. Meerson, A. N. Korolkov, M. M. Babich, and L. P. Nevskaya (Light Metals), 1966, (3), 34-46). [In Russian.] Addition of tungsten to cobalt-tungsten carbide alloys increases the hardness and improves their cutting properties. Substitution of tungsten for 10% of cobalt increases the bending strength from 155 to 164 kg. mm.², but further additions reduces it to 126 kg. mm.² at 25% tungsten, and the alloy is rendered more porous. For cutting without impact an addition of up to 25% tungsten may be used, but for surface stripping the permissible maximum is 11%. Sintering at 1400° C. in hydrogen gives the best results. Addition of tungsten to the corresponding nickel alloys also has a beneficial effect, the best properties being obtained when the free tungsten content is 15% of the nickel content, e.g. the alloy with tungsten carbide 91-4, nickel 7-30, and tungsten 1-30%. The cutting properties of the nickel alloys are as good as, and in some cases better than, those of the cobalt alloys. - D. N. S.</i>																			
ASS-61A METALLURGICAL LITERATURE CLASSIFICATION																			
100000 110 000 000										100000 110 000 000									
100000 110 000 000										100000 110 000 000									

107

The influence of excess tungsten on Pabedit and substitution of nickel for cobalt G. A. Mikhom, A. M. Korol'kov, M. M. Babich and L. P. Nevskaya *Russkii Metal* 3, No. 3, 38-40 (1960). W-C alloys were prepd with Co-W alloys contg. 0-25% W or Ni-W alloys contg. 0-42% W as binders. The addn. of W to the binder increased the hardness and improved the cutting properties. D. and strength increased up to about 10-15% W and then decreased. H. W. Rathmann

CLASSIFICATION

Hard alloys with a complex carbide component. G.
A. Meerson. Russ. 50,245, Dec. 31, 1930. Powd-
er oxides of salts not reducible by H₂ (e.g., of Ti or Zr) and
oxides of salts that are easily reduced by H₂ (e.g., W or Mo)
are heated with C. The reduction and carburization
are accelerated by introducing into the original mixt.
at least two oxides of salts that can be reduced by H₂ but
do not form carbides (Cu, Ag, Co, Ni). The metals of
the Fe group in this addit. must not exceed 5% (by vol.)
with respect to the carbide formed, while Cu or Ag must
not exceed 5% (by vol.) with respect to all the cementing
metals in the alloy.

ASO SLA METALLURGICAL LITERATURE CLASSIFICATION

Ca

Making titanium carbide. G. A. Moorman and Va. M. Lightner, J. Applied Chem (U. S. S. R.) 12, 1759-67 (1960)

French, 17(9)(1939).—TiO₂ was heated for 0 to 4 hrs. to 1700-1900° in an atm. of H with C of various types, such as lampblack, carbon black and sugar carbon. Upon gradually heating the mixt. up to 1300 or 1400° and then up to 1800 to 1900° a "titanium carbide" was produced with a combined-C content of 18-18.5%. For the prepn. of the best fine-grained Ti carbide expose the mixt. to the above max. temp. for only a short time. The C diffuses into the solid phase rapidly at these temps. A. A. B.

ASST. SEC. METALLURGICAL LITERATURE CLASSIFICATION

RESEARCH DIVISION

RESEARCH DIVISION

MEYERSON4G8A8

600

1. MEYERSON, G.A., ZVEREV, G.O., ZUFKOVA, F.M.
2. USSR (600)

Moscow Institute of Fine Chemical Technology, "Study of the Solubility of Complex Tantalum Fluoride and Niobium Fluoride", Tsvet. Met. 14, No 8, August 1939

9. ~~SECRET~~ Report U-1506, Oct. 4, 1951

1ST AND 2ND ORDERS																										3RD AND 4TH ORDERS																									
PROCESSIES AND PROPERTIES INDEX																																																			
CA Physico-mechanical properties of hard alloys of the "Pohedit" type in relation to chemical composition and heat treatment. G. A. Mccrum and V. I. Shalagin. <i>Tsvetnyy Metal.</i> 1968, No. 3, 77-85. An investigation was made to det. the influence of various methods of manufg. WC-Co alloys ("Pohedit" type) with varying Co content on their phys., mech. and cutting properties. It was established that: (1) Max. hardness, which increases with decreasing Co content, max. toughness, which increases with increasing Co content, and optimum cutting properties (on cast iron) of the alloys with the Co content of 4 to 13% are obtained at 1450° sintering temp.; (2) at this temp. the sintering of medium size articles can be completed in 45 min.; (3) increasing the temp. above 1450° results in grain growth and impairment of the properties; (4) the best cutting properties (on cast iron) are obtained in alloys with 4 to 8% Co.; and (5) reheating of hot pressed alloys at the same temp. is beneficial, as it improves the soundness and refines the grain. 4 references. H. N. Danilov 9																																																			
ASB-15.6 METALLURGICAL LITERATURE CLASSIFICATION																																																			

C

Behavior of titanium carbide in hard alloys G. A. Meerson, G. L. Zverev and B. E. Osinoyskaya J. Appl. Metal Chem. (U. S. S. R.) 13, 60-75 (in German, 75) (1940). Ti carbide contg. 19.2% C and a small amt. of residual O was obtained at 1420° and 0.14 mm. pressure. It was more granular than ordinary commercial prepreg because of the low temp. of formation. The best carbide for use in sintered alloys is low in O. The better the quality of TiC, the higher is the degree of penetration of fused Co.

A. A. Podgorny

CA

9

The oxidation refining of antimony G. A. Mironov,
I. Ya. Krol and O. R. Krein *J. Applied Chem.* (USSR
S. R.) 13, 323 (in French, 325) (1940). The admixts
of As and Fe can be removed from Sb by blowing air
through the molten metal in the presence of soda slag,
under the following optimal conditions: temp. 950°C,
velocity of air passing through molten metal 500 cc. min.
per kg. of metal, two changes of slag each amounting to
20% of soda and duration 1 hr. per change of slag (total
2 hrs.). The yield of refined Sb was 80.5% of 99.8%
purity, 8.75% of Sb was absorbed in slag and 1.75% was
evaporated as Sb₂O₃. The presence of soda was necessary for
a more complete removal of Fe and especially of As.

A. A. Polgorny

ADDITIONAL LITERATURE CLASSIFICATION

1ST AND 2ND ORDERS

PROCESS AND PROPERTIES INDEX

3RD AND 4TH ORDERS

ca

Reduction of the oxides of metals of high melting points with calcium hydride. G. A. Meerson, G. A. Kats and A. V. Khokhlova. *J. Applied Chem.* (U.S.S.R.) 13, 1770 (1940) (French, 1770 (1940)). TiO_2 , V_2O_5 , Cr_2O_3 and Ta_2O_5 were reduced with CaH_2 in H₂ at atm. pressure in elec. furnaces. The most favorable conditions were: for TiO_2 , 950-1075°; for V_2O_5 , 1025-1175°; for Cr_2O_3 , 950-1075° (in all of the above cases a 50% excess of the 80% CaH_2 , and duration of heating 45 min. to 1 hr.); for Ta_2O_5 , heating with 40% CaH_2 obtained by heating to incandescence $\text{CaO} + \text{Mg}$ in H₂ to 1025-1100° for 1 hr. Hydrogenated metals in which metal + H amounts to 90% are obtained under the most favorable conditions. The amt. of H combined with Ti reaches about 4%, with V (1H and 1H₂), H combined with V in amts. of about 1.2-2%, with Cr 1.1-4%, and with Ta 0.5-1.2%. The products of reduction are obtained in the form of homogeneous fine crystalline powders (the major portion has a grain size of up to 0.001 mm.) which can easily be freed of CaO by treatment with dil. HCl. A. A. Bozhilnik.

450 51.4 METALLURGICAL LITERATURE CLASSIFICATION

68000 51.001.000

68000 51.001.000

68000 51.001.000

68000 51.001.000

CA

PROCESSES AND PROPERTIES INDEX

Hard alloys. G. A. Meerton. Russ. 48,006, Jan. 61
 (U.S.S.R.) A fine grain Ti carbide contg. up to 17% C, is
 made by heating TiO₂ to incandescence with an excess of C
 black, adding W or Mo, and heating to 1400-1600°

AS - 31.8 METAL THERMAL TREATMENT CLASSIFICATION

Study of Conditions of Carburization of Titanium. G. A. Morrison and Ya. M. Lipkes. Henry Brucher (Altadena, Calif.), Translation No. 2099, 1948, 22 pages. From *Zhurnal Prikladnoi Khimii* (Journal of

Applied Chemistry), v. 14, no. 3, 1941, p. 291-301. Describes investigation on maximum saturation of titanium carbide with carbon, as attainable in the heating of a mixture of titanium dioxide and carbon black at atmospheric pressure in a H_2 or a CO atmosphere, respectively. Discusses reasons for nonuniformity and poor quality of industrial titanium carbide and ways of improving the present production process.

PROCESSES AND PROPERTIES INDEX																									
<i>CA</i> The formation of solid solutions in the system titanium-oxygen-carbon and conditions for obtaining titanium carbide for the production of hard alloys. G. A. Altschul. <i>Ann. sci. anal. phys.-chim., Inst. chim. g.m. (U.S.S.R.)</i> 16, No. 1, 197 319 (1943). When TiO₂ is heated with C it tends to give homogeneous solid solns. composed of TiO and TiC when the content of bound C rises above 10%. No Ti is liberated in the reaction, which goes through 3 steps, forming successively TiO₂, TiO, and TiC, with liberation of CO at each step. When a mixt. of TiO₂ + 3C is heated in a H₂ atm. from 1100° to 1800° in 20 min., almost pure TiC is formed. If heating is continued longer, TiC begins to decomp. and an impure product is obtained in a H₂ atm. some C.H.₄ is formed and helps the reaction. If any N is present, TiN will form and give an impure product. If TiO₂ and C are heated to 1850° at a pressure of 1 mm. in the absence of N, pure TiC is formed, but if any N is present and the vacuum is not good, an excess of 2-3% C must be used to give a pure product. H. M. Leicester																									
ASO 15.4 METALLURGICAL LITERATURE CLASSIFICATION																									

MEERSON, G. A.

Hard alloys, G. A. Meerson, U.S.S.R. 65,067,
Aug. 31, 1961. To an initial batch contg W and Fe to be
formed into a complex carbide (WC₂FeC) is added the
auxiliary cementing metal, Co or Ni, in a quantity less
than half its content in the final alloy. This mix is heated
in a C cartridge at 1700-2400°. The product is ground
to a size not exceeding 5μ. To this powder are added the
remaining W and auxiliary metal and the mix is processed
in the usual way for hard alloys. M. Hoesch

1ST AND 2ND SECTIONS										3RD AND 4TH SECTIONS									
PROCESSES AND PROPERTIES INDEX																			
CA Conditions of carburization of titanium. III. G. A. Meerson and Ya. M. Lipkes. <i>J. Applied Chem. (U.S.S.R.)</i> 18, 24-31(1945).—The reaction of TiO_2 with C was studied as the means of production of TiC. The processes proceed in H_2 or CO atms. in the same manner as they do in analogous circumstances in the production furnaces (C.A. 38, 2243⁹), although under production conditions the atm. contg. N causes a more deep-seated decarbonization. G. M. Kosolapoff																			
18																			
ASS-11A METALLURGICAL LITERATURE CLASSIFICATION																			
100000 *A										100000 *A									
100000 *A										100000 *A									

1ST AND 2ND CROSS		PROCESSING AND PROPERTY INDEX		3RD AND 4TH CROSS	
18		CA Conditions for carbonization of titanium. IV. G. A. Mironov and Ya. M. Lipkes. <i>J. Applied Chem. (U.S.S.R.)</i> 18, 251-8(1945)(English summary); cf. C.A. 39, 411K. Carbonization of Ti was studied at 1900° by heating Ti₃C mixt. in a CO-H₂ atm. Max. amt. of the carbide by C (at 19.5% C) occurs in the very beginning of the process; this value of bound C gradually drops to about 17%. Decarburization by H treatment showed that products are formed which have "empty" places in the TiC lattice. Decarburization in CO causes partial replacement of the displaced C atoms by O. Treatment under factory conditions, where H₂ occurs as a result of C displacement by N; this may lead to a drop of C content to 14-15%. At 2000° TiC is not stable at atm. pressure and for prepn. of pure TiC vacuum carbonization is necessary. O. M. Kozlovskii			
MATERIALS INDEX		METALLURGICAL LITERATURE CLASSIFICATION			
10000 HLP DIV 000		10000 HLP DIV 000			
10000 HLP DIV 000		10000 HLP DIV 000			

MEYERSON, G. A.

71 1/2 1/2

USSR/Metals

Jul 48

Metal Powders

Pressing Machinery

"M. Yu. Bal'shin's Book 'Powdered Metal Studies,'"
G. A. Meyerson, Dr Tech Sci, 4 pp

"Stal'" No 7

Book discusses theory of two important processes in powder metallurgy--pressing and sintering. Despite defects mentioned, book is superior to US and German works in same field. Published by Metallurgizdat, Moscow, 1948, 332 pp.

6/49T85

MEYERSON, G. A.

USSR/Chemistry - Analysis

Det 50

"Determination of Free Carbon in Boron Carbide,"
G. A. Meyerson, G. V. Samsonov, Moscow Inst of
Nonferrous Metals and Gold imeni M. I. Kalinin

"Zavod Lab" No 12, pp 1423-1428

Studied oxidation rate of differently granulated
boron carbide with oxygen and chromium anhydride.
Established that rate is const at given temp.
Method was developed for volumetric and gravimetric
detn of free carbon in boron carbide, using dif-
ferences in rate and character of oxidation pro-
cesses for boron and graphite.

182T4

CA

Determination of free carbon in boron carbide. V. A. Mereson and G. V. Samsonov (M. I. Kalinin Inst. Non Ferrous Metals and Gold, Moscow). *Zavodskaya Lab.* 16, 1423-4 (1950).—The rate of oxidation of B carbide is constant at const. temp. independently of the grain size, when O or chromate soln. were used. The rate is less than that of graphite oxidation. A soln. of CrO_3 in H_2O is added at 100° to the sample, followed by H_2SO_4 , and the resulting gases are swept by a current of dried air through the CuO absorber.

followed by the drying train of P_2O_5 , followed by $NaOH$ absorbers, $CaCl_2$ tube, and a safety vessel. The absorbers are periodically weighed. The results are plotted and the value of free C is detd. as the difference between the total C oxidized up to the given instant and the product of the time (min.) and the rate of oxidation of C (per min.). Oxidation can be done with O at 900-1000° provided that the sample is well powdered (325 mesh or better). Accuracy of 0.5% is claimed. G. M. Kosolapoff

G.A. MEYERSON, G.B. SAMS: NOV

Jul 52

USSR/Chemistry - Zirconium

"Obtaining Zirconium Carbide in a Vacuum," Moscow Inst. of Nonferrous Metals and sold
in M. I. Kalinin

Zhur Prik Khim, Vol 25, No. 7, pp 744-748

By observing the rate of increase of CO given off in calcining of a mixture of ZrO_2 and carbon black, it was found that the reaction $ZrO_2 + 3C = ZrC + 2CO$ is additive and is composed of successive reactions in which Zr_2O_3 and ZrO are formed. The practical temp. range in which the reaction with formation of ZrC will proceed in a vacuum was established and the intermediate reactions were discovered. It is possible to obtain ~~ZrC~~ by the vacuum process ZrC which contains no N or O admixtures. A fundamental error was found in the work of Prescott and Hincke (Chem. Soc., vol 40) who suggest equil coexistence of ZrO_2 and ZrC in the same reaction

263 T 44

MEYERSON, G.A.

FILYAND, M.A.; SEMENOVA, Ye.I.; POGODIN, S.A., zaslushennyy deyatel' nauki i tekhniki, professor, doktor, retsentsent; MEYERSON, G.A., professor, doktor, laureat Stalinskoy premii; SAMSONOV, G.V., redaktor; KAMAYEVA, O.M., redaktor; MIKHAYLOVA, V.V., tekhnicheskiiy redaktor.

[Properties of rare elements; handbook] Svoistva redkikh elementov: spravochnik. Moskva, Oos. nauchno-tekhn. izd-vo lit-ry po cherno i tsvetnoi metallurgii, 1953. 414 p. (MLRA 7:11)
(Chemical elements)

Received for publication, December 10, 1968

10-11-12-13-14-15-16-17-18-19-20-21-22-23-24-25-26-27-28-29-30-31-32-33-34-35-36-37-38-39-40-41-42-43-44-45-46-47-48-49-50-51-52-53-54-55-56-57-58-59-60-61-62-63-64-65-66-67-68-69-70-71-72-73-74-75-76-77-78-79-80-81-82-83-84-85-86-87-88-89-90-91-92-93-94-95-96-97-98-99-100-101-102-103-104-105-106-107-108-109-110-111-112-113-114-115-116-117-118-119-120-121-122-123-124-125-126-127-128-129-130-131-132-133-134-135-136-137-138-139-140-141-142-143-144-145-146-147-148-149-150-151-152-153-154-155-156-157-158-159-160-161-162-163-164-165-166-167-168-169-170-171-172-173-174-175-176-177-178-179-180-181-182-183-184-185-186-187-188-189-190-191-192-193-194-195-196-197-198-199-200-201-202-203-204-205-206-207-208-209-210-211-212-213-214-215-216-217-218-219-220-221-222-223-224-225-226-227-228-229-230-231-232-233-234-235-236-237-238-239-240-241-242-243-244-245-246-247-248-249-250-251-252-253-254-255-256-257-258-259-260-261-262-263-264-265-266-267-268-269-270-271-272-273-274-275-276-277-278-279-280-281-282-283-284-285-286-287-288-289-290-291-292-293-294-295-296-297-298-299-300-301-302-303-304-305-306-307-308-309-310-311-312-313-314-315-316-317-318-319-320-321-322-323-324-325-326-327-328-329-330-331-332-333-334-335-336-337-338-339-340-341-342-343-344-345-346-347-348-349-350-351-352-353-354-355-356-357-358-359-360-361-362-363-364-365-366-367-368-369-370-371-372-373-374-375-376-377-378-379-380-381-382-383-384-385-386-387-388-389-390-391-392-393-394-395-396-397-398-399-400-401-402-403-404-405-406-407-408-409-410-411-412-413-414-415-416-417-418-419-420-421-422-423-424-425-426-427-428-429-430-431-432-433-434-435-436-437-438-439-440-441-442-443-444-445-446-447-448-449-450-451-452-453-454-455-456-457-458-459-460-461-462-463-464-465-466-467-468-469-470-471-472-473-474-475-476-477-478-479-480-481-482-483-484-485-486-487-488-489-490-491-492-493-494-495-496-497-498-499-500-501-502-503-504-505-506-507-508-509-510-511-512-513-514-515-516-517-518-519-520-521-522-523-524-525-526-527-528-529-530-531-532-533-534-535-536-537-538-539-540-541-542-543-544-545-546-547-548-549-550-551-552-553-554-555-556-557-558-559-560-561-562-563-564-565-566-567-568-569-570-571-572-573-574-575-576-577-578-579-580-581-582-583-584-585-586-587-588-589-590-591-592-593-594-595-596-597-598-599-600-601-602-603-604-605-606-607-608-609-610-611-612-613-614-615-616-617-618-619-620-621-622-623-624-625-626-627-628-629-630-631-632-633-634-635-636-637-638-639-640-641-642-643-644-645-646-647-648-649-650-651-652-653-654-655-656-657-658-659-660-661-662-663-664-665-666-667-668-669-670-671-672-673-674-675-676-677-678-679-680-681-682-683-684-685-686-687-688-689-690-691-692-693-694-695-696-697-698-699-700-701-702-703-704-705-706-707-708-709-710-711-712-713-714-715-716-717-718-719-720-721-722-723-724-725-726-727-728-729-730-731-732-733-734-735-736-737-738-739-740-741-742-743-744-745-746-747-748-749-750-751-752-753-754-755-756-757-758-759-760-761-762-763-764-765-766-767-768-769-770-771-772-773-774-775-776-777-778-779-780-781-782-783-784-785-786-787-788-789-790-791-792-793-794-795-796-797-798-799-800-801-802-803-804-805-806-807-808-809-810-811-812-813-814-815-816-817-818-819-820-821-822-823-824-825-826-827-828-829-830-831-832-833-834-835-836-837-838-839-840-841-842-843-844-845-846-847-848-849-850-851-852-853-854-855-856-857-858-859-860-861-862-863-864-865-866-867-868-869-870-871-872-873-874-875-876-877-878-879-880-881-882-883-884-885-886-887-888-889-890-891-892-893-894-895-896-897-898-899-900-901-902-903-904-905-906-907-908-909-910-911-912-913-914-915-916-917-918-919-920-921-922-923-924-925-926-927-928-929-930-931-932-933-934-935-936-937-938-939-940-941-942-943-944-945-946-947-948-949-950-951-952-953-954-955-956-957-958-959-960-961-962-963-964-965-966-967-968-969-970-971-972-973-974-975-976-977-978-979-980-981-982-983-984-985-986-987-988-989-990-991-992-993-994-995-996-997-998-999-1000-1001-1002-1003-1004-1005-1006-1007-1008-1009-1010-1011-1012-1013-1014-1015-1016-1017-1018-1019-1020-1021-1022-1023-1024-1025-1026-1027-1028-1029-1030-1031-1032-1033-1034-1035-1036-1037-1038-1039-1040-1041-1042-1043-10

Impact of the new law on the
 + the 1990s. C. 1990s.

54. State of New York County of Westchester City of New York.

SC: _____ (W-)

MEYERSON, G.A.; KISLYAKOV, I.P.

Investigation of the mechanical wear of powdered-metal hard alloys
subjected to friction. Tren. i isn.mash. no.9:59-71 '54. (MLBA 7:9)
(Powder metallurgy) (Steel alloys) (Mechanical wear)

PIEYERSON, J. H.

Chemical Abst.
Vol. 48 No. 9
May 10, 1954
General and Physical Chemistry

Mechanism of the formation of titanium carbide in vacuo.
G. A. Messing and O. R. Kohn. *J. Appl. Chem. U.S.*
S.R. 29, 143-54 (1962) (Engl. translation).—See C.A. 47,
4705c. H. L. H.

Zhm. Prikl. Khim.

For 2-57
HPP

MEYERSON, G. A.

✓ Properties of the system of borides of titanium and zirconium. G. A. Meyerson, G. V. Samsonov, and R. B. Kotel'nikov (M. I. Kalinin Inst. Non-Ferrous Metals and Coal, Moscow). *Izvest. Sektora Fiz.-Khim. Anal. Inst. Obshchei i Neorg. Khim. Akad. Nauk S.S.S.R.* 25, 89-93 (1984).
The relation of corrosion, microhardness, and elec. resistance to compn. of the system of borides of Ti and Zr shows that this system is a continuous series of solid solns. Microstructure and x-ray data also show this. R. Meyeris

2

MEYERSON, G. A.

USSR

Vacuum Thermal Production of Borides of Refractory Metals. G. A. Meyerson and G. V. Semakova (Zhur. Priklad. Khim., 1984, 27, (10), 1115-1120). (In Russian). The borides of Ti, Zr, V, Nb, and Ta were prepared by vacuum reduction of the corresponding oxides with B_2C (78-2% B) + soot (99-9% C) in a graphite resistor furnace. The oxides had the following compn. (in %): (1) TiO_2 , 84.25, Fe_2O_3 , 0.75, CaO trace; (2) ZrO_2 , 97.9, CaO 0.43, TiO_2 , 0.35, Fe_2O_3 , 0.14, SiO_2 trace; (3) V_2O_5 , 89.15, Fe_2O_3 , 0.25, TiO_2 , 0.03, CaO trace; (4) Nb_2O_5 , 98.90, Ta_2O_5 , 0.66, TiO_2 , 0.27, Fe_2O_3 , 0.10; (5) Ta_2O_5 , 97.35, Nb_2O_5 , 2.23, SnO_2 , 0.91, SiO_2 , 0.73, TiO_2 , 0.68, Fe_2O_3 , 0.10. The course of the reaction was followed by measuring the pressure of the CO produced; results are given for TiB_2 . At 1400°C. and above, 1 hr. heating was sufficient for the formation of TiB_2 ; the product contg. 30.5-31.5% B, ~0.02% C. Similar results were obtained for ZrB_2 . X-ray analysis gave the following values for the lattice const. (hexagonal structure): TiB_2 , $a = 3.020$, $c = 3.217$ kX, $c/a = 1.065$; ZrB_2 , $a = 3.172$, $c = 3.638$ kX, $c/a = 1.146$. The mean particle size was 2.2-2.3 μ , with 70-90% between 1.5 and 3 μ ; $d = 4.44$ and 6.24 for TiB_2 and ZrB_2 , resp. The data obtained for the VB_2 , NbB_2 , and TaB_2 produced were, resp., as follows: B contents, 22-23, 18-20, 10-31%; C contents, 0.09, 0.17, 0.16%; $a = 3.000$, 3.080, 3.082 kX; $c = 3.060$, 3.304, 2.239 kX; $c/a = 1.027$, 1.073, 1.075; mean particle size 1.86, 1.80, 2.41; $d = 4.66$, 6.80, 11.85. Because of the high volatility of WO_3 , it was first reduced to WO_2 ; the boride obtained had a compn. near to W_2B_5 , mean particle size 2.4, $d = 11.96$, and lattice const. $a = 3.00$, $c = 13.80$ kX.—G. V. E. T.

Chem

4
0

1/11/84

1/11/84

MEYERSON, G. A.

USSR/ Chemistry Solubility

Card : 1/1

Authors : Zhdanov, G. S., Meyerson, G. A., Zhuravlev, N. N., and Samsonov, G. V.

Title : Solubility of boron and carbon in boron carbide $B_{12}C_3$ (B_4C)

Periodical : Zhur. fiz. khim. 28, Ed. 6, 1076 - 1082, June 1954

Abstract : X-ray investigations were conducted to determine the possibility and solubility limits for B and C in B_4C and to explain the mechanism of the latter with respect to the solubility of components in a covalent chemical compound. The fact that the solution takes place by displacement of C-atoms in 1b positions by B-atoms and consequent formation of B_4C of the $B_{13}C_2$ composition, was established on the basis of roentgenograms. More detailed results are given in graphs. Eleven references: 7 USSR, 2 USA and 2 German. Table, drawing, illustrations.

Institution : The M. I. Kalinin Institute of Non-Ferrous Metals and Gold and the Mechanical Institute, Moscow

Submitted : September 19, 1953

MEYERSON, G.A.

USSR/Engineering - Machining material

Card 1/1 : Pub. 86 - 5/40

Authors : Meyerson, G. A., Prof.

Title : Hard alloys

Periodical : Priroda 43/4, 45-51, Apr 1954

Abstract : A solution is offered for the prevention of the softening of the edges of high-speed steel tools through the use of carbides of metals with a high-melting point (2,600 - 3,800° C). An account is given of the making and testing of carbides of Co, Cr, W alloys and many others. The microstructure of these materials is analyzed. The articles are enumerated that are made from these materials. Six USSR references (1827-1953). Graph; drawing; illustrations.

Institution :

Submitted :

MEYERSON, G.A., professor, doktor nauk.

[Technology of making items of pure beryllium and beryllium oxide for use in nuclear reactors; reports of Soviet delegates to the International Conference on the Peaceful Uses of Atomic Energy]
Tekhnologiya polucheniia izdelii iz chistykh berillia i okisi berillia dlia ikh primeneniia v iadernykh reaktorakh; doklady predstavlennye SSSR na Mezhdunarodniu konferentsiiu po mirnomu ispol'zovaniu atomnoi energii. Moskva, 1955. 8 p. [Microfilm] (MLRA 10:5)

1. Interantional Conference on the Peaceful Uses of Atomic Energy, Geneva, 1955.

(Beryllium)

MEYERSON, O.A.

[Metalloceramics of thorium] Metallokeramika toria; doklady.
predstavlenyye SSSR na Mezhdunarodnuu konferentsiiu po mir-
nomu ispol'zovaniu atomnoi energii. Moskva, 1955. 13 p.
[Microfilm] (Thorium--Metallurgy) (MLRA 9:3)

PHASE I BOOK EXPLOITATION 820

Meyerson, Grigoriy Abramovich, and Zelikman, Abram Naumovich

Metallurgiya redkikh metallov (Metallurgy of Rare Metals) Moscow, Metallurgizdat, 1955. 608 p. 5,500 copies printed.

Reviewers: Bol'shakov, K. A., Doctor, Professor, Abrikosov, N. Kh., Doctor of Chemical Sciences, Maslyanitskiy, I. N., Doctor, Professor, Greyver, N. S., Doctor, Professor; Ed.: Vysotskaya, V. N.; Ed. of Publishing House: Kamayeva, O. M.; Tech. Ed.: Attopovich, M. K.

PURPOSE: This book is recommended as a textbook for students at metallurgical institutes and may also be useful to engineers and technicians.

COVERAGE: The book deals with the industrial production of refractory metals (tungsten, molybdenum, tantalum, niobium, vanadium, titanium, and zirconium) and the trace-associate metals (gallium, indium, thallium, germanium, selenium, tellurium, and rhenium). Physical and chemical properties are given, and fields of application are specified. The authors explain the theoretical and practical aspects of the production of pure metals and their more important alloys and chemical compounds. Chapters IV, VII, XIII-XVI, and Section 60

Card 1/13

Metallurgy of Rare Metals

820

were written by G.A. Meyerson,; Chapters I-III, V, VI, VIII-XII, XVII-XXII, by A.N. Zelikman. The authors express their thanks for suggestions received from the reviewers and from scientific workers in the Department of Metallurgy of Light Metals of the Moskovskiy institut tsvetnykh metallov i zobta (Moscow Institute of Nonferrous Metals and Gold), at the Gosudarstvennyy nauchno-issledovatel'skiy institut po redkim metallam (State Scientific Research Institute for Rare Metals), and at the Vsesoyuznyy nauchno-issledovatel'skiy institut po tverdym splavam (All-Union Scientific Research Institute for Hard Alloys). There are 375 references, of which 205 are Soviet, 126 English, 40 German, 3 French, and 1 Italian.

TABLE OF CONTENTS:

Preface	9
Introduction	11
1. Definition of the term "rare metals"	11
2. Classification of rare metals	17
3. History of the development of the rare-metals industry in the USSR	21
4. Survey of basic technological methods of extracting rare metals from ores	24
Card 2/13	

Metallurgy of Rare Metals	820
PART I. METALLURGY OF TUNGSTEN AND MOLYBDENUM	
Ch. I. General Information on Tungsten and Molybdenum	28
5. Basic historical data	28
6. Properties of tungsten and molybdenum	28
7. Properties of chemical compounds of tungsten and molybdenum	29
8. Fields of application	33
	45
Ch. II. Production of Tungsten Trioxide	
9. Tungsten minerals, ores, and concentrates	49
10. Methods of treating tungsten concentrates	49
11. Decomposition of tungsten concentrates	54
12. Removal of impurities from solutions	57
13. Precipitation of tungsten compounds from solutions	63
14. Treatment of scheelite concentrates	66
15. Cost of producing tungstic anhydride (WO_3)	72
16. Removal of impurities from tungstic acid and production of tungsten trioxide	78
	80
Ch. III. Production of Chemical Compounds of Molybdenum	
17. Molybdenum minerals and ores and their concentration	85
18. Survey of methods of treating molybdenum concentrates	85
19. Oxidizing roasting of molybdenum concentrates	90
20. Production of pure molybdenum trioxide	91
Card 3/13	102

Metallurgy of Rare Metals 820

21. Extraction of molybdenum from low-grade concentrates and from industrial tailings	114
22. Treatment of wulfenite concentrates	118
Ch. IV. Production of Metallic Tungsten and Molybdenum	
23. Physical and chemical basis of the hydrogen reduction of tungstic anhydride	119
24. Process of reducing tungstic anhydride by hydrogen	119
25. Methods of controlling the particle size of tungsten powder	125
26. Hydrogen reduction of molybdic anhydride	135
27. Physical and chemical conditions for the carbon reduction of tungstic anhydride	137
28. Process of reducing tungstic anhydride by carbon	140
29. Electrolytic methods of obtaining tungsten and molybdenum	145
30. Production of compact ductile tungsten	149
31. Production of compact ductile molybdenum by the metal-ceramic method	151
32. Fused molybdenum	177
	179

Card 4/13

Metallurgy of Rare Metals 820

PART II. METALLURGY OF TANTALUM AND NIOBIUM (COLUMBIUM)

Ch. V. General Information on Tantalum and Niobium	
33. Historical data	184
34. Properties of tantalum and niobium	184
35. Properties of chemical compounds of tantalum and niobium	184
36. Fields of application of tantalum and niobium	187
	191
Ch. VI. Production of Chemical Compounds of Tantalum and Niobium	
37. Minerals, ores, and concentrates of tantalum and niobium	193
38. Products of the treatment of ore concentrates	193
39. Survey of methods for decomposing tantalite-columbite concentrates	197
40. Fusion of tantalite-columbite with sodium hydroxide	197
41. Fusion of tantalite-columbite with potassium hydroxide or potassium carbonate	199
42. Separation of tantalum and niobium	204
43. Decomposition of tantalite-columbite with hydrofluoric acid	206
44. Treatment of titanium-niobium concentrates	216
45. Separation of titanium from niobium and tantalum	217
46. Chlorination of titanium-tantalum-niobium concentrates	219
	220

Card 5/ 13

Metallurgy of Rare Metals 820

Ch. VII. Production of Metallic Tantalum and Niobium	
47. Basic data on thermal reduction processes	223
48. Sodium-reduction method of producing tantalum powder	224
49. Electrolytic production of tantalum powder	231
50. Comparison of the sodium-reduction and electrolytic methods of producing tantalum	235
51. Magnesium reduction of tantalum pentachloride	240
52. Production of metallic niobium	241
53. Production of compact ductile tantalum	243
54. Recovery of metallic tantalum from tailings	247
	255

PART III. METALLURGY OF VANADIUM

Ch. VIII. General Information on Vanadium	256
55. Properties of vanadium	256
56. Chemical compounds of vanadium	256
57. Fields of application of vanadium	257
	262

Card 6/ 13

Metallurgy of Rare Metals

820

Ch. IX. Treatment of Vanadium Ores and Concentrates	
58. Minerals, ores, and concentrates	264
59. Extraction of vanadium from iron ores	264
60. Production of pure ductile metallic vanadium	266
	279

PART IV. METALLURGY OF TITANIUM AND ZIRCONIUM

282

Ch. X. General Information on Titanium and Zirconium	
61. Basic historical data	282
62. Properties of titanium and zirconium	282
63. Chemical compounds of titanium and zirconium	282
64. Fields of application of titanium and zirconium	288
	298
Ch. XI. Production of Chemical Compounds of Titanium	
65. Titanium minerals, ores, and concentrates	305
66. Products of the treatment of titanium concentrates	305
67. Survey of methods for decomposing titanium concentrates	307
68. Production of titanium dioxide from ilmenite	308
69. Production of titanium dioxide from sphene and perovskite	311
70. Production of titanium tetrachloride	324
Card 7/13	325

Metallurgy of Rare Metals

820

Ch. XII. Production of Chemical Compounds of Zirconium	
71. Minerals, ores, and concentrates	332
72. Products of the treatment of zirconium concentrates	332
73. Methods of decomposing zirconium concentrates	335
74. Decomposition of zircon by fusion with sodium hydroxide	335
75. Decomposition of zircon by sintering with lime	336
76. Separation of zirconium from solutions	339
77. Preparation of potassium fluozirconate	341
78. Preparation of zirconium tetrafluoride	345
79. Separation of hafnium from zirconium	346
	353
Ch. XIII. Production of Powdered and Spongy Titanium and Zirconium	
80. Calcium reduction of titanium dioxide	358
81. Calcium reduction of zirconium dioxide	359
82. Reduction of titanium dioxide and zirconium dioxide with calcium hydride	363
83. Reduction of titanium tetrachloride	364
84. Magnesium reduction of zirconium tetrachloride	366
85. Sodium reduction of potassium fluozirconate	377
86. Electrolytic production of titanium and zirconium	383
87. Inflammability of titanium and zirconium powder and rules for safe handling	386
Card 8/13	391

Metallurgy of Rare Metals

820

- Ch. XIV. Production of Compact Ductile Titanium and Zirconium
- 88. Thermal dissociation of iodides 392
 - 89. Metal-ceramic method of producing ductile titanium 392
 - 90. Production of ductile titanium by the melting method 398
 - 91. Metal-ceramic method of preparing ductile zirconium 400
 - 92. Production of ductile zirconium by the melting method 407
 - 93. Comparison of the various methods of producing ductile titanium and zirconium 410

PART V. ALLOYS OF REFRACTORY METALS

- Ch. XV. Carbon-free and Low-Carbon Alloys of Refractory Metals 415
- 94. Alloys of tungsten and molybdenum 419
- 95. Alloys of tantalum and niobium 419
- 96. Titanium-base alloys 429
- 97. Zirconium-base alloys 432
- Ch. XVI. Carbide-base Hard Alloys 444
- 98. Cast carbides of tungsten 448
- 99. Metal-ceramic hard alloys (cermets) 448
- 100. Granular mixtures for surfacing with hard alloys 453
- 101. Heat-resistant and scale-resistant alloys with a titanium carbide base 480

Card 9/13

481

Metallurgy of Rare Metals 820

PART VI. TRACE-ASSOCIATE METALS

Ch. XVII. Gallium	487
102. Properties of gallium	487
103. Chemical compounds of gallium	487
104. Fields of application of gallium	489
105. Naturally-occurring sources of gallium	490
106. Extraction of gallium from tailings of alumina production	492
107. Extraction of gallium from the residual anode alloy obtained in the electrolyte refining of aluminum	494
108. Extraction of gallium from the tailings of zinc production	498
109. Preparation of pure compounds of gallium	501
110. Preparation of metallic gallium	502
Ch. XVIII. Indium	503
111. Properties of indium	503
112. Chemical compounds	504
113. Fields of application of indium	504
114. Naturally-occurring sources of indium	507
115. Extraction of indium from tailings of the pyrometallurgical production of zinc	509
116. Extraction of indium from tailings of the hydrometallurgical production of zinc	510
Card 10/13	516

Metallurgy of Rare Metals 820

117. Electrolytic extraction of indium from solutions	522
Ch. XIX. Thallium	
118. Properties of thallium	523
119. Chemical compounds of thallium	523
120. Fields of application of thallium	524
121. Naturally-occurring sources of thallium	527
122. Methods of extracting thallium from industrial tailings	528
123. Extraction of thallium from the tailings of zinc production	529
124. Extraction of thallium and cadmium from dust produced in the smelting of zinc in shaft furnaces	530
125. Extraction of thallium from dust formed in the roasting of pyrites	535
Ch. XX. Germanium	537
126. Properties of germanium	537
127. Chemical compounds of germanium	537
128. Fields of application of germanium	540
129. Raw materials	543
130. Extraction of germanium from the tailings of zinc production	545
131. Extraction of germanium from the tailings of coal concentrates	547
132. Preparation of metallic germanium	551
Card 11/13	556

Metallurgy of Rare Metals	820
133. Preparation of high-purity germanium and germanium monocrystals with specific electrical properties	557
134. Treatment of germanium tailings	566
Ch. XXI. Selenium and Tellurium	
135. Properties of selenium and tellurium	566
136. Chemical compounds	566
137. Fields of application	569
138. Sources of selenium and tellurium	573
139. Extraction of selenium and tellurium from anode slimes forming in the electrolytic refining of copper	575
140. Extraction of selenium from dusts forming at sulfuric acid plants and sulfite cellulose plants	586
141. Extraction of selenium from gold-containing ores	589
Ch. XXII. Rhenium	
142. Discovery of rhenium	590
143. Properties of rhenium	590
Card 12/13	590

Metallurgy of Rare Metals

820

- 144. Chemical compounds of rhenium 591
- 145. Fields of application of rhenium 594
- 146. Raw materials 595
- 147. Technology of extracting rhenium from tailings 596
- 148. Preparation of metallic rhenium 596

Bibliography

AVAILABLE: Library of Congress 598

Card 13/13

GO/mas
11-6-58

MEYERSON, G A.

The index metal

18

of the metal

MEYERSON, G. A.

27
 Manufacturing articles of pure beryllium and beryllium
 oxide for use in nuclear reactors. G. A. Meyerson, G. E.
 Kaplan, G. P. Smith, and O. D. Schmitt. *U.S. Pat.*
 2,840,000. *Chem. Abstr.* 55:10,400 (1955).
 described. Articles are made from BeO by (1) forming in
 graphite molds, and firing at 1800°. (2) pressing BeO in
 graphite molds at 1800° and under pressure of 12-20 kg/
 sq. cm., (3) pressing under 10-15 mm. Hg at 1800-1900°
 under 15-20 kg./sq. cm. Pure Be was obtained by ex-
 trusion of molten chlorides. Articles for use in nuclear reactors
 to be used at high temperatures. Articles for use in nuclear reactors
 in graphite-molded articles fired at 1800°. The
 residual thermal stresses are eliminated by vacuum anneal-
 ing at 1800° and slow cooling. Articles for use at lower tempera-
 tures are made by hot-pressing in open air at 1800° under 5 tons/
 sq. cm. Rods and pipes are extruded in the hot state from
 the billets obtained by metallurgical methods.
 Alexis N. Pestoff

Rmk MT

MEYERSON, G. A. and SMIRNOV, M. P.

"An investigation of the mechanism of the electrolytic preparation of borides of the high melting metals", Khimiya Redkikh Elementov, No. 2, p 130, 1955.

The above mechanism was studied on an example of preparation of titanium borides by the electrolysis of a molten mixture $2B_2O_3 + CaO + CaF_2 + TiO_2$. On the basis of the results obtained, the mechanism of the formation of borides during electrolysis was elucidated.

SO: D-413171

MEYERSON, G. A.

USSR

2137. A method of producing boron nitride. G. A. MEYERSON, G. V. SASSONOV, and N. YA. TRITINA (*Ogneupory*, 20, 72, 1955). Methods of producing BN are summarized; the best method is considered to be treatment of a batch of $B_2O_3 + CaO + NH_4Cl$ with NH_3 at $1,100^\circ - 1,200^\circ C$. The batch is made by sintering together B_2O_3 and CaO obtained by heating H_3BO_3 with chalk, the decomposition of the hydrate and the carbonate resulting in a fine distribution of B_2O_3 between the CaO particles and partial formation of Ca borate. It is claimed that this method results in a 92-93% yield of BN. It is stated that BN cannot be sintered into dense specimens by hot-pressing under normal conditions, since at high temperatures BN dissociates and takes up carbon. (2 fig., 7 tables.)

MEYERSON, G. A. and KOLCHIN, O. P.

"ON the Physicochemical Principles of the Process of Reducing Chemically Stable Oxides with Calcium Hydride," Sbornik Nauchnykh Trudov, Moskovskiy Institut Tsvetnykh Metallov i Zolota imeni M. I. Kalinin, No. 25, 1955

MEYERSON, G.A.

27 15
 11
 4E2C
 1-fra
 11
 11

Vacuum-thermal production of borides of refractory metals, and investigation of several boride systems. G. A. Meyerson, G. V. Sushakov, R. B. Kotelnikov, and N. A. Tseltina. *Sbornik Nauch. Trudov Moskov. Univ. Fizichesk. Matem. i Zolota 1955, No. 25, 200-25; Referat. Zhur., Met.* 1956, Abstr. No. 9158. — The conditions of production of borides of Ti, Zr, V, Nb, Ta, and W, and the binary systems of certain borides were studied. Briquets of metal oxide, B₂O₃, and C black were charged into a vacuum elec.-resisting furnace. The optimal conditions of boride production were found from tensiometric data. X-ray analysis of the powders of borides Ti, Zr, V, Nb, and Ta showed lattice constants agreeing with those in the literature. The ds. of the borides determined by micropycnometer agreed with the calcul. ds. W boride, on account of volatility of W oxides, was obtained at much lower temp. with the excess of WO₃. It has the approx. compn. W₁₀B₁₂ with the lattice const. $a = 3.00 \text{ \AA}$, and $c = 13.80 \text{ \AA}$, and d. 12.96. Alloys of systems TiB₂-ZrB₂, TaB₂-ZrB₂, and TiB₂-NbB₂ were prepd. by hot-pressing with subsequent annealing; all were monophasic, and their lattice const. were linearly proportional to their compn. The alloys were comparatively corrosion-resistant, this resistance changing gradually with the compn. The microhardness graph of the system changes continuously. The diagram of compn. vs. elec. cond. is a continuous curve with convex upward. This indicates that the borides form a continuous series of solid solus. A. N. Pestoff

PAZUKHIN, Vasilii Aleksandrovich; FISHER, Aleksandr Yakovlevich; KRESTOVNIKOV, A.M., professor, doktor, retsenzent; MEYERSON, G.A., professor, doktor, retsenzent; ZHUKOVSKIY, Ye.I., professor, doktor, retsenzent; MEN'SHIKOV, M.I., kandidat tekhnicheskikh nauk, retsenzent; SAMSONOV, G.V., kandidat tekhnicheskikh nauk, retsenzent; MESHCHERYAKOV, S.I., kandidat tekhnicheskikh nauk, retsenzent; SAMSONOV, G.V., redaktor; ARKHANGEL'SKAYA, M.S., redaktor izdatel'stva; BIRLOV, A.P., tekhnicheskiiy redaktor

[Vacuum in metallurgy] Vakuum v metallurgii. Moskva, Gos. nauchno-tekhn. izd-vo lit-ry po chernoi i tsvetnoi metallurgii, 1956. 520 p.
(Vacuum) (Metallurgy) (MLBA 9:12)

AL'TGAUZEN, O.N., kandidat fiziko-matematicheskikh nauk; BERNSTEYN, M.L., kandidat tekhnicheskikh nauk; BLANTER, M.Ye., doktor tekhnicheskikh nauk; BOKSHTAYN, S.Z., doktor tekhnicheskikh nauk; BOLKHOVITINOVA, Ye.M., kandidat tekhnicheskikh nauk; BORZDYKA, A.M., doktor tekhnicheskikh nauk; BUNIN, K.P., doktor tekhnicheskikh nauk; VINOGRAD, M.I., kandidat tekhnicheskikh nauk; VOLOVIK, B.Ye., doktor tekhnicheskikh nauk [deceased]; GAMOV, M.I., inzhener; GELLER, Yu.A., doktor tekhnicheskikh nauk; GORELIK, S.S., kandidat tekhnicheskikh nauk; GOL'DENBERG, A.A., kandidat tekhnicheskikh nauk; GOTLIB, L.I., kandidat tekhnicheskikh nauk; GRIGOROVICH, V.K., kandidat tekhnicheskikh nauk; GULYAYEV, B.B., doktor tekhnicheskikh nauk; DOVGALYEVSKIY, Ya.M., kandidat tekhnicheskikh nauk; DUDOVTSSEV, P.A., kandidat tekhnicheskikh nauk; KIDIN, I.N., doktor tekhnicheskikh nauk; KIPNIS, S.Kh., inzhener; KORITSKIY, V.G., kandidat tekhnicheskikh nauk; LANDA, A.F., doktor tekhnicheskikh nauk; LEYKIN, I.M., kandidat tekhnicheskikh nauk; LIVSHITS, L.S., kandidat tekhnicheskikh nauk; L'VOV, M.A., kandidat tekhnicheskikh nauk; MALYSHEV, K.A., kandidat tekhnicheskikh nauk; MEYERSON, G.A., doktor tekhnicheskikh nauk; MINKOVICH, A.N., kandidat tekhnicheskikh nauk; MOROZ, L.S., doktor tekhnicheskikh nauk; NATANSON, A.K., kandidat tekhnicheskikh nauk; MAKHIMOV, A.M., inzhener; MAKHIMOV, D.M., kandidat tekhnicheskikh nauk; POGODIN, ALEKSEYEV, G.I., doktor tekhnicheskikh nauk; POPOVA, Y.M., kandidat tekhnicheskikh nauk; POPOV, A.A., kandidat tekhnicheskikh nauk; RAKHSHTADT, A.G., kandidat tekhnicheskikh nauk; ROGEL'BERG, I.L., kandidat tekhnicheskikh nauk;

(Continued on next card)

AL'TGAUZEN, O.N.---- (continued) Card 2.

SADOVSKIY, V.D., doktor tekhnicheskikh nauk; SALT'YKOV, S.A.,
 inzhener; SOBOLEV, N.D., kandidat tekhnicheskikh nauk; SOLODIKHIN,
 A.G., kandidat tekhnicheskikh nauk; UMANSKIY, Ya.S., kandidat
 tekhnicheskikh nauk; UTEVSKIY, L.M., kandidat tekhnicheskikh nauk;
 FRIDMAN, Ya.B., doktor tekhnicheskikh nauk; KHIMYSHIN, F.F.,
 kandidat tekhnicheskikh nauk; KHRUSHCHEV, M.M., doktor tekhnicheskikh nauk; SHAPIRO,
 M.M., inzhener; SHKOL'NIK, L.M., kandidat tekhnicheskikh nauk;
 SHRAYBER, D.S., kandidat tekhnicheskikh nauk; SHCHAPOV, N.P., doktor
 tekhnicheskikh nauk; GUDTSOV, N.T., akademik, redaktor; GORODIN, A.M.,
 redaktor izdatel'stva; VAYNSHTYIN, Ye.B., tekhnicheskii redaktor

[Physical metallurgy and the heat treatment of steel and iron; a
 reference book] Metallovedenie i termicheskaya obrabotka stali i
 chuguna; spravochnik. Pod red. N.T.Dudtsova, M.L.Bernshteina, A.G.
 Rakhshadtat. Moskva, Gos. nauchno-tekhn. izd-vo lit-ry po chernoi i
 tsvetnoi metallurgii, 1956. 1204 p.
 (MLRA 9:9)

1. Chlen -korrespondent Akademii nauk USSR (for Bunin)
 (Steel--Heat treatment) (Iron--Heat treatment)
 (Physical metallurgy)

MEYERSON, G. A.

Category : USSR/Solid State Physics - Diffusion. Sintering

E-6

Abs Jour : Ref Zhur - Fizika, No 3, 1957, No 6690

Author : Meyerson, G.A.

Title : On Certain Problems in the Theory of Sintering.

Orig Pub : Poroshkovaya metallurgiya, Yaroslavl', 1956, 11-30

Abstract : Survey, devoted to a discussion of the fundamental outlines of the mechanism of the sintering process. Bibliography. 29 titles.

Card : 1/1

MEYERSON, G. A. Prof.

"Ways for the Development of Titanium Production, " by Prof G. A. Meyerson, Khimicheskaya Nauka i Promyshlennost', Vol 1, No 5, Sep/Oct 56, pp 496-504

After reviewing briefly the uses of titanium and pointing out its corrosion resistance, the heat resistance of titanium carbide and its use as a material for the construction of gas turbines, the advantages of titanium as a construction material, and the advantageous properties of titanium alloys as far as mechanical strength is concerned, the author discusses in some detail the technology of titanium production, mainly on the basis of non-USSR publications. Starting with a review of procedures for the production of titanium from rutile and ilmenite, he subjects to consideration methods for the production of ductile titanium, the metal-ceramic (metal powder) method for the production of ductile titanium, reduction of titanium tetrachloride with sodium in the gas phase or on the surface of sodium chloride forming a fluidized solid bed in the reduction furnace, the electrolytic separation of titanium, and the thermal decomposition of titanium halides (particularly TiI_4).

[Comment: The technology of titanium production is of importance by reason of the potential application of high-melting titanium derivatives, alloys, and cermets at nuclear energy power plants and nuclear energy installations in general. For instance, titanium carbide may be used in gas turbines operated by nuclear power.]

Sum 1219

MEYERSON, G. A.

5
1-482c
✓ Powder-Metallurgical Hard Metals with a Non-Uniform
Distribution of the Carbide Phase for the Manufacture of
Abrasive Materials. G. A. Meyerson and G. Y. Samsonov.
Izv. Akad. Nauk S.S.S.R. 1966, Tekhn., (4), 121-125. —
In Russian. The conditions of prepn. of these materials
were studied. In grinding the abrasive material, projections
with higher wear resistance are formed on the surface of the
hard metal, holding back in the matrix the less wear-resistant
but more brittle parts. This type of structure
improves the wear resistance than homogenous
hard metal. A. B.

PM RG
MT
JP

Meyerson, G.A.

AUTHOR: MEYERSON, G.A., KOLCHIN, O.P. PA - 2307
TITLE: On the Mechanism of the Reduction of the Oxides of Zirconium and Titanium by Calcium-hydride. (O mekhanizme vostanovleniya okislov tsirkoniya i titana gidridom kal'tsiya, Russian).
PERIODICAL: Atomnaya Energiya, 1957, Vol 2, Nr 3, pp 253 - 259 (U.S.S.R.)
 Received: 4 / 1957 Reviewed: 5 / 1957
ABSTRACT: On the basis of the example of these reduction processes the theoretical basis of the reduction of the chemically stable metal oxides by calcium-hydride is investigated. The present paper studies the physical-chemical conditions for the use of calcium-hydride as reduction means of zirconium- and titanium oxides. The question as to whether calcium hydride (as a means of reduction of higher energy) is more advantageous than calcium, mainly in connection with the separation of atomic hydrogen during the decomposition of calcium-hydride, is above all investigated. The thermo-dynamics of the reduction processes mentioned in the title and the experiments carried out when investigating the mechanism of the reactions are discussed. The following results are obtained from these investigations:
 1) By means of the thermodynamic computation of these reduction processes and by means of special experiments the reducing activity of the calcium-hydride and of the calcium liberated during its thermal dissociation and of the atomic hydrogen was determined. The decrease of the free energy during the interaction of atomic

Card 1/3

Meyerson, G.A.

Distri 4520

Study of heterogeneous reactions, with application of grinding and mixing (acid decomposition of scheelite).
G. A. Meyerson and R. A. Pavlyuk. *Zhur. Neorg. Khim.* 2, 1371-2 (1967).--Equil. conditions in the reaction $\text{CaWO}_4 + \text{HCl} \rightleftharpoons \text{H}_2\text{WO}_4 + \text{CaCl}_2$ are studied. This reaction is used in scheelite decompn. in heated ball mills. It is found that scheelite decompn. does not require high HCl concns, as previously used.
A. Volbachev

41

Em

3
1

MEYERSON, G. A.

AUTHORS: Meyerson, G. A. and Khavskiy, N. N.

136-3-8/25

TITLE: Study of Ways of Improving the Acid Method of Treating Scheelite. (Izucheniye putey usovershenstvovaniya kislotnogo metoda pererabotki sheelita).

PERIODICAL: Tsvetnyye Metally, 1957, No.3, pp.41 47 (USSR)

ABSTRACT: The decomposition of scheelite concentrates with acids is not applied industrially. The authors consider that one of the causes hindering such processes is the action of H_2WO_4 films formed on scheelite grains. Preliminary experiments showed that decomposition with hot hydrochloric acid in bath mills avoided this effect and this method was adopted in the investigation described. 650-ml capacity porcelain ball mills were used, the materials treated being concentrates from the Chelyabinsk and Chorukh-Dayron beneficiation works, with 47.1 and 42.32% WO_3 , respectively. The results obtained are represented by plots against time of: degree of decomposition at various temperatures; final hydrochloric acid concentration for 20 and 10% excesses of acid; degrees of decomposition of roasted and unroasted concentrates and for treatment with and without balls in the mill. Tabulations of results are also given. A two-stage treatment was also studied and results for each stage are tabulated.

1/2

Study of Ways of Improving the Acid Method of Treating Scheelite. 136-3-8/25

The work showed the possibility of a single stage decomposition of scheelite at 100 C and with a quantity of hydrochloric acid 120% of theoretical, 99-100% of the WO_3 being extracted into the ammoniacal solution under laboratory conditions. 1 to 2% final acid concentration gave practically complete decomposition. With the conditions selected for the two-stage decomposition similar results were obtained. This technique is recommended for use when the plant is being worked very intensively, since it enables rapid final extraction with high acid concentrations and excesses to be achieved in the second stage. It is suggested that ball-mills can be operated at atmospheric pressure under reflux condensers and that with acid leaching ammonia and not soda should be used for neutralization; hydrochloric acid could be regenerated by treating the waste liquid ($CaCl_2 + HCl$) with sulphur acid. Because of the advantages of the acid leaching technique its full scale testing is recommended.

2/2 There are 5 figures, 8 tables and 3 references, 5 of which are Slavic.

AVAILABLE: Library of Congress

MEYERSON, G.A.

AUTHOR
TITLE

MEYERSON, G.A., KAPLAN, G.Ye., USPENSKAYA, T.A. 69-9-15/X
Improvement of the Alkali Decomposition Process of
Monazite.

(Usovershenstvovanie protsessa shchelochnogo razlozheniya
monatsita).

PERIODICAL

Atomnaya Energiya, 1957, Vol 1, Nr 9, pp 259-260 (USSR)

ABSTRACT

The initial material, a monazite concentration, had a granulation of 1-5 mm. As a decomposing medium NaOH (50 g/l) was used at a temperature of 130°C. First, the concentration was treated in a heatable ball mill (1,5 l cubic capacity, diameter 0,8 cm, weight 1,5 kg), which was mounted in a lift thermostat. Experimentally 4 hours duration was found to be the optimum. It was further proved by experiment that the decomposition of the concentrate (> 99,5 %) is best if the consumption of NaOH is 150 - 200 % of the weight of the initial concentrate. For a further reduction of the consumption of NaOH a further two-step treatment was used. During the first step 75 % of the weight of the initial material was used as NaOH weight. The not soluble remains of this step were collected (from 10 fillings) and were

CARD 1/2